

SHANGRAO RUICHEN SEALING CO.,LTD DONGGUAN RUICHEN SEALING CO.,LTD

Address: Road 8.Yanshan Industrial Estate, Shangrao City, 334500, Jiangxi Prov., CHINA

Tel: +86-18024335478 E-mail: aaron@dgork.com

MATERIALS TEST REPORT

NBR70 BLACK (N7001-1) COMPOUND

ASTM D2000 M2BG 714 A14 B14 E014 E034 EA14 F19

Press Cure	Post Cure Sheet : 1 hrs 120°C Button : 1 hrs 120°C		
Sheet : 5min 170°C			
Button : 10 min 170°C			
ORIGINAL PROPERTIES	SPECIFICATION	TEST RESULT	ASTM TEST METHOD
HARDNESS SHORE A	70°±5	70	D2240
TENSILE STRENGTH, MPA, MIN	≥14	13.54	D412
ULTIMATE ELONGATION, %, MIN	≥250	229.57	D412
SPECIFIC GRAVITY (g/cm3)		1.20	D297
HEAT RESISTANCE 70 H . AT 100°C (A14)			D573
CHANGE IN HARDNESS, POINTS	+/-15	6	
CHANGE IN TENSILES STRENGTH, %	+/-30	-18.39	
CHANGE IN ULTIMATE ELONGATION,MAX %	-50	-31.48	
COMPRESSION SET, MAX, 22H AT 100°C(B14)	≤25	6.82	D395
FLUID RESISTANCE NO.1 OIL, 70H AT 100°C (EO14)			D471
CHANGE IN HARDNESS, POINTS	-5~+10	2	
CHANGE IN TENSILES STRENGTH, MAX %	-25	-2.36	
CHANGE IN ULTIMATE ELONGATION,MAX %	-45	-15.43	
CHANGE IN VOLUME %	-10~+5	1.87	
FLUID RESISTANCE NO.3 OIL, 70H AT 100℃ (EO34)			D471
CHANGE IN HARDNESS, POINTS	-10~+5	-11 G29	
CHANGE IN TENSILES STRENGTH, MAX %	-45	-46.45 133	
CHANGE IN ULTIMATE ELONGATION,MAX %	-45	-29.08	
CHANGE IN VOLUME %	0~+25	41.2	
WATER RESISTANCE:100℃,70H (EA14)			D471
CHANGE IN HARDNESS, POINTS	±10	+3	
CHANGE IN VOLUME %	±15	-3.98	
LOW-TEMPERATURE BRITTLENESS NONBRITTLE			
AFTER 3MIN AT -55°C (F19)			D2137

Remark:

- 1. The data are based on testing slabs I buttons and are for reference purpose only..
- 2. Our compound can meet above -mentioned ASTM 2000 Spec.
- 3. This information is, to the best of our knowledge, accurate reliable to the date indicated.
- 4. The above mentioned data have been obtained by tests we consider as reliable, We don't assure that
- the same results can be obtained other laboratories, using different conditions by the preparation and -evaluation of the samples.

Approved By: Frankie Fang Checked By: Yunli Tu Tested By: Jianjun Zhu